

NV 900 SPECIFICATIONS



Designed for continuous air disinfection and odor control in medium indoor spaces, the Novaerus Protect 900 uses patented filter-free ultra-low energy plasma technology with a 2-speed fan.



MODEL

NV900

Placed on stand or wall mounted

Supplied with 8.2 ft power cord

ELECTRICAL RATING

120 VAC, 60 Hz, 1.07 A

Fuse Rated at 250 VAC, 3 Amps, Listed

POWER CONSUMPTION

20 watts

CONSTRUCTION + COLOR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish

DIMENSIONS + WEIGHT

14.4" w x 14.4" h x 4.5" d

10.4 lbs.

ELECTRICAL CONNECTION

Switched and fused with a grounded, molded

3 pin power cord

FAN AIR FLOW VOLUME

SPEED I: 150 ft³/min

SPEED II: 180 ft³/min

OPERATING CONDITIONS

10-35°C, 10-75% Relative Humidity, 2000m

SHIPPING / STORAGE CONDITIONS

5°C-50°C, Maximum 95% Relative Humidity

QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 and OHSAS 18001

This air cleaner complies with the federal ozone emissions limit, ARB certified

Authorized Distributor

MEDformance.com

info@medformance.com

+1 (800) 795-1486